



6" APPROVED MATERIAL
COMPACTED TO 95%
DENSITY OF STANDARD
PROCTOR. STABILIZE IF
P.I. IS ABOVE 12.

8" REINFORCED
CONCRETE 5-SACK,
3000 PSI, NO. 4
REBAR AT 24" O.C.B.W.

"X" = 8" REINFORCED CONCRETE 5-SACK 3000 PSI
NO. 4 REBAR 24" O.C.B.W.
12" DOWEL UNLESS POUR MONOLITHICALLY WITH
CONCRETE PAVEMENT

"Y" = 2" TYPICAL WITH 6" CROWN
1-1/2" WHEN 3" CROWN IS USED
WITH CONCRETE PAVEMENT
OR AT A 4-WAY INTERSECTION WITH
REDUCED CROWN

8' CONCRETE VALLEY GUTTER

TYPICAL SECTION
NTS



PREPARED BY: THE CITY OF SULPHUR SPRINGS ENGINEERING DEPARTMENT

CITY OF SULPHUR SPRINGS
DEVELOPMENT MANAGEMENT MANUAL
DETAIL DRAWINGS

8' CONCRETE
VALLEY GUTTER

SCALE: NTS
DATE: 11.21.2013
DR. BY:
CK. BY:

DRAWING NUMBER

FIG.-4.04